

Giving Shape to Ideas





OACI AICAA	
bizhub C3110	The bizhub® C3110 brings more color power to your desktop, with
	brilliant image quality at up to 32 ppm, Emperon print controller,
	PageScope® software for account management, even optional Super G3
	fax - all combined in compact, space-saving design that's a perfect fit
	for mixed MFP and desktop environments.

	Spec	

System Specifications	
System memory	1 GB (standard) / 2 GB (maximum)
System hard disk	320 GB (optional)
Interface	10-Base-T/100-Base-TX/1,000-Base-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4 / IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Reversing automatic document feeder	Up to 50 originals, 4" x 6" to 8.5" x 11", 50-110 gsm
Printable paper size	4" x 6" to 8.5" x 14" / custom paper sizes
Printable paper weight	60-210 gsm
Paper input capacity	Standard: 350 sheets Max.: 850 sheets
Tray 1	250 sheets / 4" x 6" to 8.5" x 11" / 60-210 gsm
Tray 2 (optional)	500 sheets / Letter, Legal / 60-90 gsm
Manual bypass	100 sheets / 4" x 6" to 8.5" x 14" / custom paper sizes / 60-210 gsm
Automatic duplexing	Letter, legal / 60-210 gsm
Output capacity	Max.: 150 sheets
Copy/print volume	Max.:120,000 pages / month ¹
Toner lifetime	Black: 6,000 pages / CMY: 6,000 pages
Imaging unit lifetime	Black: 30,000 pages / CMY: 30,000 pages
Power consumption	110 V / 60 Hz, Less than 900 W (system)
System dimensions	19.7" x 17.6" x 21.4" (H x W x D)
System weight	Approx. 76 lb

Copier Specifications

pi	
Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD Polymerized Toner
Print speed	Up to 32 ppm (Letter, mono/color)
Autoduplex speed	Up to 32 ppm (Letter, mono/color)
1st copy out time	13 sec./17 sec. (mono/color)
Warm-up time	Approx. 38 sec. ²
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1-99
Original format	4" x 6" to 8.5" x 14"
Magnification	25-400% in 1% steps; auto zooming
Copy functions	Duplex copy, ID card copy, 2-in-1, 4-in-1, poster, density adjustments

Printer Specifications

•	
Print resolution	1,200 x 1,200 dpi, 600 x 600 dpi
Page description	PCL5e/c, Adobe [®] PostScript 3 [™] , PDF 1.7, XPS ⁴
Operating systems	Windows (x32/x64): VISTA / 7 / 8
	Windows Server (x32/x64): 2003 / 2012 ³
	Macintosh OS X 10.x or later
	Linux
	Citrix
Printer fonts	80 PCL Latin, 137 Adobe® PostScript 3™ Latin
Print functions	Direct Print4 of PDF, JPEG, TIFF, XPS4 and OOXML (DOCX, XLSX, PPTX),
	secure print⁴, combination, n-up, overlay, watermark

Scanner Specifications

Scan speed	Up to 31 opm (mono/color)
Scan resolution	600 x 600 dpi
Scan modes	Scan-to-email, Scan-to-SMB, Scan-to-FTP, Scan-to-USB, Scan-to-HDD, Scan-to-DPWS, Network TWAIN
File formats	TIFF, PDF, Compact PDF, JPEG, XPS
Scan Destinations	250 (shared with fax), LDAP support

Fax Specifications

Fax	Super G3 (optional)
Transmission	Analog, PC-fax
Resolution	Max: 600 x 600 dpi
Compression	MH, MR, MMR, JBIG
Modem	up to 33.6 Kbps
Destinations	250 (shared with scan), LDAP support
Functions	Polling, time shift, PC-Fax

Uptions	
PF-14 Paper Tray	Letter, Legal / 500 sheets / up to 90 gsm
SCD-25 Copier Desk	Ensures ergonomic height and provides storage space for print media, etc.
HD-P06 Hard Disk	320 GB HDD ⁴
1 GB Expanded Memory	1 GB memory extension for faster processing
FK-512 Fax Kit	Supports G3 fax communication (requires MK-P04 mount kit)
MK-P04 Fax Mount Kit	Installation kit for fax board
ID Card Reader	Various ID card technologies ⁴
LK-106 Barcode Fonts	Supports native barcode printing ⁴
LK-107 Unicode Fonts	Supports native Unicode printing ⁴
LK-108 OCR A and B fonts	Supports native OCR A and B font printing ⁴
LK-111 ThinPrint® Client	Print data compression for reduced network impact
SX-4600WAN Wireless LAN	Wireless LAN to network connector
CS-1 Convenience Stapler	Convenient stapling of up to 50 prints per set

System Features	
Security	ISO 15408 EAL3 (in evaluation) ⁴ , IP filtering and port blocking, SSL2 ⁴ , SSL3 ⁴ and TSL1.0 network communication ⁴ , IPsec support ⁴ , IEEE 802.1x support ⁴ , user authentication ⁴ , secure print ⁴ ,
	HDD overwrite (8 standard types) ⁴ , HDD data encryption ⁴
Software	PageScope Net Care Device Manager, PageScope WebConnection, PageScope Data Administrator, PageScope Direct Print,

¹ Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guidline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446














² Warm-up time may vary depending on the operating environment and usage

³ Supports x64 only

⁴ HD-P06 optional hard disk enables secure printing, proof-then-print, print & hold, job storing, XPS emulation, i-Option support and ID card reader support